



United States Environmental Protection Agency
Washington, DC 20460

PLUGGING AND ABANDONMENT PLAN


Name and Address of Facility

Resolute Natural Resources Company
1675 Broadway, Suite 1950, Denver, CO 80202

Name and Address of Owner/Operator

Resolute Aneth, LLC.
23429 County Road G, Cortez, CO 81321

Locate Well and Outline Unit on
Section Plat - 640 Acres



State Utah County San Juan Permit Number _____

Surface Location Description

1/4 of 1/4 of 1/4 of SW 1/4 of Section 17 Township 40s Range 24e

Locate well in two directions from nearest lines of quarter section and drilling unit

Surface

Location 740 ft. frm (N/S) N Line of quarter section
and 1665 ft. from (E/W) E Line of quarter section.

TYPE OF AUTHORIZATION

- ☐ Individual Permit
☒ Area Permit
☐ Rule

Number of Wells 34

WELL ACTIVITY

- ☐ CLASS I
☒ CLASS II
☐ Brine Disposal
☒ Enhanced Recovery
☐ Hydrocarbon Storage
☐ CLASS III

Lease Name Aneth Unit

Well Number See attachments

CASING AND TUBING RECORD AFTER PLUGGING

SIZE	WT (LB/FT)	TO BE PUT IN WELL (FT)	TO BE LEFT IN WELL (FT)	HOLE SIZE
13 3/8	48		100' to 500'	
8 5/8	24 to 36		1200' to 1600'	
5 1/2	14 to 15.5		5500' to 6000'	

METHOD OF EMPLACEMENT OF CEMENT PLUGS

- ☒ The Balance Method
☐ The Dump Bailer Method
☐ The Two-Plug Method
☐ Other

CEMENTING TO PLUG AND ABANDON DATA:

	PLUG #1	PLUG #2	PLUG #3	PLUG #4	PLUG #5	PLUG #6	PLUG #7
Size of Hole or Pipe in which Plug Will Be Placed (Inches)	5 1/2	5 1/2	5 1/2	5 1/2			
Depth to Bottom of Tubing or Drill Pipe (ft.)	5450	4600	1550	53			
Sacks of Cement To Be Used (each plug)	11.5	11.5	11.5	11.5			
Slurry Volume To Be Pumped (cu. ft.)	13.7	13.7	13.7	13.7			
Calculated Top of Plug (ft.)	5350	4500	1450	3			
Measured Top of Plug (if tagged ft.)							
Slurry Wt. (Lb./Gal.)	15.6	15.6	15.6	15.6			
Type Cement or Other Material (Class III)	A	A	A	A			

LIST ALL OPEN HOLE AND/OR PERFORATED INTERVALS AND INTERVALS WHERE CASING WILL BE VARIED (if any)

From	To	From	To
Perfs 5425'	5500'		

Estimated Cost to Plug Wells

Casing, cement and pipe configuration are for typical injection wells without laterals. Estimated net average P&A cost for these wells is \$34,013 per well.

Certification

I certify under the penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment. (Ref. 40 CFR 144.32)

Name and Official Title (Please type or print)

Dwight E Mallory, EH&S Coordinator

Signature


Date Signed

2/26/2008

RESOLUTE

NATURAL RESOURCES

Sample Vertical UIC Well - P&A Schematic
Intermediate Casing Set Above Chinle Top
Production Casing Cement to Top Hermosa




NOTES:

Formation, Casing and Cement depths are typical for wells in the Aneth Unit
13 3/8" Surface Casing is standard. However, 10 3/4" and 13" casing may be present in a limited number of wells.
8 5/8" Intermediate Casing is standard. However, 7", 8" and 9 5/8" may be present in a limited number of wells.
5 1/2" Production Casing is standard. However, 4 1/2" casing may be present in a limited number of wells.

RESOLUTE

NATURAL RESOURCES

Sample Vertical UIC Well - P&A Schematic
Surface Casing Set Above Chinle Top
Cement to Surface




NOTES:

Formation, Casing and Cement depths are representative of wells in the permit area and are for illustration purposes only
13 3/8" Surface Casing is standard. However, 10 3/4" and 13" casing may be present in a limited number of wells.
8 5/8" Intermediate Casing is standard. However, 7", 8" and 9 5/8" may be present in a limited number of wells.
5 1/2" Production Casing is standard. However, 4 1/2" casing may be present in a limited number of wells.

RESOLUTE

NATURAL RESOURCES

Sample Vertical UIC Well - P&A Schematic
8 5/8" Surface Casing
Cement to Surface



NOTES:

Formation, Casing and Cement depths are typical for wells in the Aneth Unit
8 5/8" Surface Casing is standard. However, 9 5/8", 10 3/4" and 13 3/8" casing may be present in a limited number of wells.
5 1/2" Production Casing is standard. However, 4 1/2" casing may be present in a limited number of wells.



United States Environmental Protection Agency
Washington, DC 20460

PLUGGING AND ABANDONMENT PLAN


Name and Address of Facility

Resolute Natural Resources Company
1675 Broadway, Suite 1950, Denver, CO 80202

Name and Address of Owner/Operator

Resolute Aneth, LLC.
23429 County Road G, Cortez, CO 81321

Locate Well and Outline Unit on
Section Plat - 640 Acres



State

Utah

County

San Juan

Permit Number

Surface Location Description

1/4 of 1/4 of 1/4 of SW 1/4 of Section 17 Township 40s Range 24e

Locate well in two directions from nearest lines of quarter section and drilling unit

Surface

Location 740 ft. frm (N/S) N Line of quarter section
and 1665 ft. from (E/W) E Line of quarter section.

TYPE OF AUTHORIZATION

- ☐ Individual Permit
☒ Area Permit
☐ Rule

Number of Wells 34

Lease Name Aneth Unit

WELL ACTIVITY

- ☐ CLASS I
☒ CLASS II
☐ Brine Disposal
☒ Enhanced Recovery
☐ Hydrocarbon Storage
☐ CLASS III

Well Number See attachments

CASING AND TUBING RECORD AFTER PLUGGING

SIZE	WT (LB/FT)	TO BE PUT IN WELL (FT)	TO BE LEFT IN WELL (FT)	HOLE SIZE
13 3/8	48		100' to 500'	
8 5/8	24 to 36		1200' 1600'	
5 1/2	14 to 15.5		5500' to 6000'	

METHOD OF EMPLACEMENT OF CEMENT PLUGS

- ☒ The Balance Method
☐ The Dump Bailer Method
☐ The Two-Plug Method
☐ Other

CEMENTING TO PLUG AND ABANDON DATA:

	PLUG #1	PLUG #2	PLUG #3	PLUG #4	PLUG #5	PLUG #6	PLUG #7
Size of Hole or Pipe in which Plug Will Be Placed (inches)	4 3/4 OH	5 1/2	5 1/2	5 1/2	5 1/2		
Depth to Bottom of Tubing or Drill Pipe (ft.)	5610	5450	4600	1600	53		
Sacks of Cement To Be Used (each plug)	10	11.5	11.5	11.5	11.5		
Slurry Volume To Be Pumped (cu. ft.)	11.8	13.7	13.7	13.7	13.7		
Calculated Top of Plug (ft.)	5510	5350	4500	1500	3		
Measured Top of Plug (if tagged ft.)							
Slurry Wt. (Lb./Gal.)	15.6	15.6	15.6	15.6	15.6		
Type Cement or Other Material (Class III)	A	A	A	A	A		

LIST ALL OPEN HOLE AND/OR PERFORATED INTERVALS AND INTERVALS WHERE CASING WILL BE VARIED (if any)

From	To	From	To
4.5 " Open Hole 5510'	7500' TMD		

Estimated Cost to Plug Wells

Casing, cement and pipe configuration are for typical injection wells with splayed laterals drilled in the Desert Creek. Estimated net average P&A cost for these wells \$43,500 per well.

Certification

I certify under the penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment. (Ref. 40 CFR 144.32)

Name and Official Title (Please type or print)

Dwight E Mallory, EH&S Coordinator

Signature


Date Signed

2/26/2008

RESOLUTE

NATURAL RESOURCES

Sample Horizontal UIC Well - P&A Schematic
Splayed Laterals in Desert Creek
Intermediate Casing Below Chinle Top
Production Casing Cement to Top Hermosa



NOTES:

Formation, Casing and Cement depths are representative of wells in the permit area and are for illustration purposes only
13 3/8" Surface Casing is common. However, 10 3/4" and 13" casing may be present in a limited number of wells.
8 5/8" Intermediate Casing is common. However, 7", 8" and 9 5/8" may be present in a limited number of wells.
5 1/2" Production Casing is common. However, 4 1/2" casing may be present in a limited number of wells.